

The color palette of the BRICK MAIN collection reinterprets the soft textures of the porcelain stoneware surfaces creating a series ranging from the pure white to deep black through the discovery of the warm and cool gray gradations. An impeccable interpretation of basic colors, BRICK MAIN is available in five colours (White, Black, Sand, Mud and Brown) with six different surface textures that enrich the weave of the material. The thickness is only 0,3" with a V1 shade variation.

BRICK MAIN is manufactured in production sites that are certified with Environmental Management Systems ISO 14001:2004 (internationally recognized standard) and EMAS (European regulation - EC Reg 1221/09).

		METODO DI PROVA TEST METHOD	VALORE PRESCRITTO DALLE NORME REQUIRED STANDARDS	VALORE MADE+39 MADE+39 VALUE
CARATTERISTICHE CHIMICHE CHEMICAL FEATURES	RESISTENZA ATTACCO CHIMICO RESISTANCE TO CHEMICALS	UNI EN ISO 10545-13	≥ GB	UA
	RESISTENZA ALLE MACCHIE RESISTANCE TO STAINS	UNI EN ISO 10545-14	≥ 3	5
CARATTERISTICHE DI SICUREZZA SAFETY FEATURES	RESISTENZA ALLO SCIVOLAMENTO COEFFICIENT OF FRICTION	DIN 51130 DIN 51097	METODO DI PROVA DISPONIBILE TEST METHOD AVAILABLE	R10
		DCOF ANSI A 137.1-2012		DCOF: ≥ 0,42
CARATTERISTICHE MECCANICHE SUPERFICIALI SURFACE MECHANICAL FEATURES	RESISTENZA ALL'ABRASIONE SU- PERFICIALE (PEI) RESISTANCE TO SURFACE ABRASION (PEI)	UNI EN ISO 10545-7	DICHIARAZIONE DEL FABBRICANTE DECLARATION OF MANUFACTURER	IV
CARATTERISTICHE MECCANICHE MASSIVE BULK MECHANICAL FEATURES	SFORZO DI ROTTURA BREAKING STRENGTH	UNI EN ISO 10545-4	S ≥ 1300 N	S ≥ 2000 N