

The BRICK TEXT collection is inspired by heavy woven fabrics in various colors, in a line of wall and floor coverings in the 4"x12" size that reinterpret the textures of interior decorating materials. The glazed porcelain tile collection is available in three complementary colors (White, Grey and Black) and offers 12 different textures that enrich the weave of the material.

The thickness is only 0,3" and while the White and Black shades present a V1 shade variation, the colour Grey offers a V3 shade variation that allows you to play with the colors.

BRICK TEXT is manufactured in production sites that are certified with Environmental Management Systems ISO 14001:2004 (internationally recognized standard) and EMAS (European regulation - EC Reg 1221/09).

		METODO DI PROVA TEST METHOD	VALORE PRESCRITTO DALLE NORME REQUIRED STANDARDS	VALORE MADE+39 MADE+39 VALUE
CARATTERISTICHE CHIMICHE CHEMICAL FEATURES	RESISTENZA ATTACCO CHIMICO RESISTANCE TO CHEMICALS	UNI EN ISO 10545-13	≥ GB	GL A
	RESISTENZA PRODOTTI USO DOMESTICO HOUSEOLD PRODUCTS RESISTANCE	UNI EN ISO 10545-14	MIN. GB	CONFORME COMPLIANT
CARATTERISTICHE DI SICUREZZA SAFETY FEATURES	RESISTENZA ALLO SCIVOLAMENTO COEFFICIENT OF FRICTION	DIN 51130	METODO DI PROVA DISPONIBILE TEST METHOD AVAILABLE	R10
		DCOF ANSI A 137.1-2012		DCOF: ≥ 0,42
CARATTERISTICHE MECCANICHE SUPERFICIALI SURFACE MECHANICAL FEATURES	RESISTENZA ALL'ABRASIONE SU- PERFICIALE (PEI) RESISTANCE TO SURFACE ABRASION (PEI)	UNI EN ISO 10545-7	DICHIARAZIONE DEL FABBRICANTE DECLARATION OF MANUFACTURER	IV*
CARATTERISTICHE MECCANICHE MASSIVE BULK MECHANICAL FEATURES	SFORZO DI ROTTURA BREAKING STRENGTH	UNI EN ISO 10545-4	S ≥ 1300 N	S ≥ 1300 N