


DECLARATION OF PERFORMANCE (DoP) 001 MADE +39

1. Unique identification code of the product-type
Dry-pressed ceramic tiles with low water absorption $E_b \leq 0,5 \%$.
2. Intended use
Ceramic tiles for flooring and wall finishes, internal and external applications.
3. Name and contact address of the manufacturer
MADE +39 srl, via Verga 12 , 41053 Maranello (MO) – ITALY
4. System of assessment and verification of constancy of performance of the construction products (AVCP)
System 4
5. Name and identification number of notified body, if applicable
Not applicable
6. Declared performance

Essential characteristics	Performance	Harmonised technical specifications
Reaction to fire	A1fl/A1	 EN 14411:2012
Release of dangerous substances		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	≥ 1300 N	
Modulus of rupture	≥ 35 N/mm ²	
Slip resistance	See Annex enclosed	
Skid resistance	NPD	
Adhesion resistance		
- Cementitious adhesive C1 class	$\geq 0,5$ N/mm ²	
Thermal shock resistance	Passed	
Durability		
- Internal use	Passed	
- External use: Frost resistance	Passed	

The performance of the product identified in point 1 is in conformity with the declared performance in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Maranello , December 30th 2016

Signed for and on behalf of the manufacturer by Marco Santinelli MADE +39,Ceramica Quality Dept.

Annex to the Declaration Of Performance N. DOP001MADE+39

Slip Resistance			
Series	Products	DIN 51130	BCRA D.M. 236/1989
BRICK TEXT	White, Black, Grey, Green,	R10	>0,49 – 0,55